

Aquaflow Permeable Block Paving

Data Sheet



Specially designed, incorporating a slot and chamfer which allows water to permeate through the finished surface at a high rate. Aesthetically similar to traditional block paving, the Aquaflow permeable block can be specified for all sites designed under BS7533-Pt13. Full ancillary kerb system to complement the range is also available. Recommended lay - 45° or 90° herringbone for all trafficked areas.

Colours


For an accurate colour match please request a sample.



Natural



Charcoal



Burnt Red




Autumn Yellow




Red Brindle



Golden Brindle



Purbeck



Vendage



Specification

Plan size (mm)	Thickness (mm)	Area per pack (m ²)	Blocks per pack	Pack weight (tonne)
200 x 100	60	8.48	424	1.1
200 x 100	80	5.92	296	1.04
Precast concrete block paving Manufactured to: BS EN 1338:2003 Tensile splitting strength 3.6 Mpa BBA certificate: 97/3373		Abrasion 60mm block Class 3 Abrasion 80mm block Class 4 Resistance to weathering Class 3 Slip/skid resistance Low		Finishes Standard finish Bush hammered finish †
		Applications Residential & commercial projects, including driveways, access roads, car parks & trafficked areas		

The Aquaflow permeable block is best used in combination with the Formpave Aquaflow System, a unique patent protected sub base design which utilises geogrids to reduce sub base depth without effecting structural strength. This system has BBA Accreditation and we offer a free bespoke design service to help you minimise your construction costs. Although every effort is made to ensure consistency of product colour, variations between production batches can occur. Formpave recommend that all products are thoroughly mixed on site by drawing from a minimum of three packs. † Special order