

Aquasett Permeable Block Paving

Data Sheet



Specially designed, incorporating a slot and chamfer which allows water to permeate through the finished surface at a high rate. Available in a wide range of colours and finishes, Aquasett offers an aesthetic appearance for all environments. Available as mixed packs or large block only. Can be specified for all sites designed under BS7533-Pt13. Full ancillary kerb system to complement the range is also available.

Colours

For an accurate colour match please request a sample.



Traditional



Purbeck



Vendage



Pennant



Red Brindle

Specification

Combined Packs		60mm (Depth)	80mm (Depth)		
Total quantity of mixed blocks per pack		434	310		
Qty of Blocks	250 x 150mm	140	100		
Per Pack	150 x 150mm	196	140		
(Ind blocks/sizes)	100 x 150mm	98	70		
Area per pack (m ²)		11.2	8.0		
Weight per pack (tonne)		1.47	1.42		
Plan size (mm)	Thickness (mm)	Area per pack (m ²)	Blocks per pack	Pack weight (tonne)	
250 x 150	60	10.5	280	1.38	
250 x 150	80	7.5	200	1.33	
Precast concrete block paving Manufactured to: BS EN 1338:2003 Tensile splitting strength 3.6 Mpa		Abrasion 60mm block Class 3 Abrasion 80mm block Class 4 Resistance to weathering Class 3 Slip/skid resistance Low		Finishes Olden finish Bush hammered finish †	Applications Residential and commercial projects including driveways, access roads and carparks

The Aquasett permeable blocks are best used in combination with the Formpave Aquaflow System, a unique patent protected sub base design which utilises geogrids to reduce sub base depth without effecting structural strength. This system has BBA Accreditation and we offer a free bespoke design service to help you minimise your construction costs. Although every effort is made to ensure consistency of product colour, variations between production batches can occur. Formpave recommend that all products are thoroughly mixed on site by drawing from a minimum of three packs. † Special order