

Ecogranite Aquasett Permeable Block Paving

Data Sheet




a Forterra brand



Ecogranite Aquasett permeable blocks are specially designed, incorporating a slot and chamfer, to allow water to disperse at a high rate whilst retaining its visual integrity. Used within residential and commercial projects including driveways, access roads and carparks, Available in mixed packs or large block only. A kerb system is also available to complement the range. The textured surface exposes the sparkling granite offering excellent skid/slip resistance. The Ecogranite Aquasett permeable block can be specified for all sites designed under BS7533-Pt13.

Colours For an accurate colour match please request a sample.



Cornish Silver Grey



Balmoral



Tintagel †



Truro *

UP TO 77% BY-PRODUCT MATERIAL

One of the most sustainable paving options currently available.



Specification

Combined Packs	60mm	80mm
Mixed blocks per pack Made up of the following sizes	434	310
250 x 150mm (blocks per pack)	140	100
150 x 150mm (blocks per pack)	196	140
100 x 150mm (blocks per pack)	98	70
Coverage per pack (m²)	11.2	8.0
Weight per pack (tonne)	1.47	1.42
Large Block Only †		
Block sizes (depth)	60mm	80mm
250 x 150mm (blocks per pack)	280	200
Coverage per pack (m²)	10.5	7.5
Weight per pack (tonne)	1.38	1.33
Precast concrete block paving Manufactured to: BS EN 1338:2003 Tensile splitting strength 3.6 Mpa	Abrasion 60mm block Class 3 Abrasion 80mm block Class 4 Resistance to weathering Class 3 Slip/skid resistance Extremely low	Finishes Bush hammered finish
		Applications 60mm thick for use on footpaths, domestic drives and 80mm thick for use on roads.

The Ecogranite Aquasett permeable blocks are best used in combination with the Formpave Aquaflow® System, a unique patent protected sub base design which utilises geogrids to reduce sub base depth without effecting structural strength. This system has BBA Accreditation and we offer a free bespoke design service to help you minimise your construction costs.

* Colour purposes only. † Special order.

Formpave

Tufthorn Avenue, Coleford
Gloucestershire, GL16 8PR

Tel: 01594 836 999
Fax: 01594 810 577

Email: sales@formpave.co.uk
Web: www.formpave.co.uk